

WEARABLE TAG

The Pozyx Wearable Tag is a small and lightweight battery powered device used for accurate positioning

It delivers reliable positioning information and combines long battery life with several wearing options to fit any tracking solution and to make tracking effortless.





TRACKING EDITION

Accurate tracking Long lasting battery Small and lightweight

INTERACTIVE EDITION

Tracking edition features + Push button Status LED (3 colors)

— Features

- Accurate UWB positioning (10-30cm)
- Configurable and context sensitive update rate
- NFC connectivity for activation and configuration
- IP20 rating (interactive) or IP65 rating (tracking)
- Ultra-low power
- Replaceable battery
- Battery life extension by motion sensing
- Battery life indication
- Several wearing options

Use Cases

ASSET TRACKING AND IDENTIFICATION IN INDUSTRY

Real-time asset tracking to improve operational efficiency, enhance productivity and workflow performance WIP MONITORING FOR OPERATIONAL EXCELLENCE

WIP dashboard visibility to automate material management and tracking of rework or expedite orders WORKFORCE EFFICIENCY FOR REDUCED LABOR COST

People tracking for optimized labor efficiency, automated time registration and improved safety WAREHOUSE MANAGEMENT AND INVENTORY CONTROL

No more searches for lost goods. Track reusable packaging and critical tools. Optimize space utilization.







Specifications

CONNECTIVITY UWB (CH2*/CH5), NFC/RFID

(*) Country dependent and potentially subject to registration and authorization.

MAX REFRESH 10 Hz

DIMENSIONS 50 × 42 × 15 mm (l × w × h)

CASING ASA

WEIGHT 23g

INGRESS IP20 (interactive)
PROTECTION IP65 (tracking)

OPERATIONAL TEMPERATURE

POWER 3V / 620 mAh battery

CR2450 coin cell

-25°C to 55°C

SENSORS Accelerometer 3-Axis 2g

10 bits (1.6 to 25 Hz)

CERTIFICATIONS CE, FCC, ISED, UKCA,

SRRC (May 2022, pending)

Mounting options

- Wristband
- Lanyard

Battery life

TRACKING EDITION

> 5 YEARS*

5 VEARS

0.5 Hz 31 MONTH

MONTHS > 5 YEARS*

1 Hz 21 MONTH

10 Hz

0.2 Hz

3 MONTHS 22 MONTHS*

EDITION

0.2 Hz

0.5 Hz 26 MONT

ONTHS > 5 YEARS

1 Hz

18 MONTHS

> 5 YEARS*

INTERACTIVE

10 Hz

3 MONTHS

22 MONTHS*

Results measured at room temperature under controlled circumstances.
*Battery life with auto-sleep feature enabled for tag being static 90% of the time, and static blink rate of 0.1 Hz

Contact

GENERAL INQUIRY

SALES DEPARTMENT

TECHNICAL SUPPORT

info@pozyx.io sales@pozyx.io

support@pozyx.io







INSTAGRAM

@pozyxlabs



TWITTER **@pozyxlabs**

